

## LCD19DM Desktop Vers.M



- optional IP65 all around
- optional projected capacitive touchscreen
- optional operating temperature -20°C to 50°C



## Specifications

### LCD Panel

Display Type	19" TFT LCD
Resolution	1280 x 1024
Colors	16.7M
Brightness	300cd/m <sup>2</sup> (typ.)
<i>option</i>	high brightness
<i>option</i>	transflective
<i>option</i>	wide viewing angle

### Interface

VGA Input	HD-Sub 15pin, DVI
<i>option</i>	Video Input - Composite, S-Video, PAL/NTSC, SDI
OSD Control	Brightness, Contrast, Phase, Size, Sharpness, Auto Adjust, etc.

### Mechanical

Construction	milled aluminium chassis, powder coated
	RAL 9005, 7035, 7032, 9006, etc.
Dimension	448 x 385 x 80mm
Mounting	VESA 100 x 100mm (4 x M4)

### Electrical

Power Supply	115/230V AC, 50Hz/60Hz
<i>option</i>	12V, 24V, 48V DC

### Environmental

Temperature	operating 0°C to 45°C storage -20°C to 60°C
Humidity	max. 90% RH, non condensing

### Options

AC adapter	
Touchscreen	resistive <b>projected capacitive</b>
Protection glass	anti glare (IP65 on frontside)
Waterproof	<b>IP65 all around</b>
Wide Temperature	<b>operating -20°C to 50°C</b>
<i>other options on request</i>	

### Accessories (included)

Power-cord
VGA-cable
DVI-cable