

TFT 9

Größe: 125 x 100 x 23 (L x B x H) in mm



Beschreibung:

- For easy plug+display connections of flatpanels to **DVI-** and **analog-RGB** sources from **VGA** up to **WUXGA** (1920x1200) incl. HDTV (**HDMI** with adapter)
- Optional **Display Port**
- Output for LVDS Displays **up to WUXGA (1920x1200)**
- Color depths up to 24bits
- Highest picture quality by improved scaling algorithm
- Simply Flatpanel configuration via software
- Single 12V power supply

Durch unsere eigene Entwicklung und Fertigung sind kundenspezifische Änderungen ab 1 Stk. nach Absprache möglich. Preise auf Anfrage.

Technische Daten:

- One product for different resolution up to WUXGA (1920 x 1200)
- Color depths up to 24bits
- Input Voltage: 8-25V (Backlight voltage = Input voltage)
- analog-RGB: 15 pin HD-SUB VGA-Connector, 10pin IDC-Connector
- DVI: DVI-Connector, 16pin IDC-Connector
- Optional Display Port
- Advanced Scaling
- On-Screen Display, 4-button user interface, OSD control for all features
- Optional IR-Remote
- High power connector for power supply and backlight converter (12V and 5V)
- Cable-Kits for flatpanels
- Backlight dimming, PWM and analog voltage
- Optional Touch-Controller for resistive Touch (4-, 5 bit), Hampshire, RS232 / USB
- 2 LED outputs
- One A/D-Channel (e.g. poti)
- 3 digital I/O Ports
- 4 Buttons for special use
- Dimensions: 125mm x 100mm
- Power supply: typ. 12V= +/- 10%
- Storage Temp. -25°C to +60°C
- Operating Temp. -10°C (-25°C) to +50°C
- Ambient Humidity 10% to 90% RH
- Storage Humidity 10% to 90% RH



Auch als TFT-Kit lieferbar, ab 1 Stk.