



LCD6MDC Minifront DC



• Optional Touchscreen



Specifications

LCD Panel

Display Type	6.5" TFT LCD
Resolution	640 x 480
<i>option</i>	1024 x 768
Colors	262k
Brightness	250cd/m ² (typ.)
<i>option</i>	up to 600cd/m ² (typ.)
Viewing Angle	130° H, 110° V (typ.)
<i>option</i>	160° H, 160° V (typ.)

Interface

VGA Input	HD-Sub 15pin, DVI
<i>option</i>	Video Input - Composite, S-Video, PAL/NTSC, SDI
OSD Control	Brightness, Contrast, Phase, Size, Sharpness, Auto Adjust, etc.

Mechanical

Front Color	Aluminium front panel powder coated, aluminium/ steel chassis
Front Dimension	RAL 9005, 7035, 7032, 9006, etc.
Cover Dimension	213 x 173 x 3mm
Mounting	209 x 155 x 60mm
Protection	Panelmount (4 x Ø3.2mm)
<i>option</i>	IP41 on frontside
	Anti glare protection glass (IP65 on frontside)

Electrical

Power Supply	12V DC
<i>option</i>	24V, 48V DC

Environmental

Temperature	Operating 0°C to 45°C
	Storage -20°C to 60°C
Humidity	max. 90% RH, non condensing

Options

Touchscreen
AC adapter
Customized front plate
other options on request

Accessories (included)

Power-cord, VGA-cable, DVI-cable